



NOTE:
STANDARD MOUNTING POSITION FOR ALL UMS TURNTABLE MODELS IS WITH HYDRAULIC DRIVE LOCATED IN THE 6 O'CLOCK POSITION. HYDRAULIC MOTOR CAN BE MOUNTED ON EITHER FRONT OR BACK OF TURNTABLE AND IS EASILY CHANGED.

OPTIONAL TURNTABLE MOUNTING POSITIONS ARE POSSIBLE BUT MAY REQUIRE LONGER HYDRAULIC HOSES AND SENSOR CONNECTIONS AND MAY ALSO REQUIRE MODIFICATION OF EXISTING MACHINE GUARDS, COVERS AND SAFETY INTERLOCK SYSTEMS.

STANDARD MOTOR MOUNTING POSITION

REAR MOUNTED MOTOR POSITION

APPROVAL PRINT REFERENCES ARE TO
MODEL # _____
SERIAL # _____

PLEASE CHECK PRINT DIMENSIONS CAREFULLY. NOTE AND INITIAL ANY CHANGES OR CORRECTIONS. PROMPT RETURN EXPEDITES DELIVERY OF YOUR ORDER.

APPD. BY _____ DATE _____

<p>PROPRIETARY & CONFIDENTIAL This is proprietary and confidential material which is the sole property of MGS, Inc. It is to be used only for the specific purpose for which it was prepared or converted for any other use without the express written approval of MGS, Inc.</p>		<p>W188 N1171 Maple Rd. Germantown, WI 53022 Phone: (262) 555-5795</p>	
<p>Description 650MM HYDRO EUROMAP Customer Approval Drawing</p>		<p>Drawn by G GIBBONS</p>	
<p>Scale 1:2</p>		<p>Used on 650 MM HYDRO</p>	
<p>Drawn Date 5/13/2007</p>		<p>Rev ---</p>	
<p>Last saved by: gibbons Last saved on: Wednesday, June 25, 2008 8:55:15 AM</p>		<p>Sheet 1 of 1</p>	