



NOTE:
STANDARD MOUNTING POSITION FOR ALL UMS TURNABLE MODELS IS WITH HYDRAULIC DRIVE LOCATED IN THE 6:00'CLOCK POSITION. HYDRAULIC MOTOR CAN BE MOUNTED ON EITHER FRONT OR BACK OF TURNABLE AND IS EASILY CHANGED.

OPTIONAL TURNABLE MOUNTING POSITIONS ARE POSSIBLE BUT MAY REQUIRE LONGER HYDRAULIC HOSES AND SENSOR CONNECTIONS AND MAY ALSO REQUIRE MODIFICATION OF EXISTING MACHINE GUARDS, COVERS AND SAFETY INTERLOCK SYSTEMS.

STANDARD MOTOR MOUNTING POSITION

APPROVAL PRINT REFERENCES ARE TO
MODEL # _____
SERIAL # _____

PLEASE CHECK PRINT DIMENSIONS CAREFULLY. NOTE AND INITIAL ANY CHANGES OR CORRECTIONS PROMPT RETURN EXPEDITES DELIVERY OF YOUR ORDER.

APPD. BY _____ DATE _____

<p>PROPRIETARY AND CONFIDENTIAL</p> <p>This is proprietary and confidential material and is the sole property of MGS, Inc. It is to be used only for the specific purpose for which it was prepared and is not to be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying, recording, or by any information storage and retrieval system, without the express written approval of MGS, Inc.</p> <p>TOLERANCES AND DIMENSIONS UNLESS OTHERWISE SPECIFIED ARE IN ACCORDANCE WITH ASME Y14.5M (1995) STANDARDS (DIMENSIONS ARE IN INCHES)</p> <p>.1 = .05 .01 = .01 .001 = .005 ANGLES = 1°</p>		<p>W188 N1701 Maple Rd. Germantown, WI 53022 Phone: (262) 555-5790</p> <p>MGS MFG. GROUP ENGINEERING FOR OPTIMUM PERFORMANCE</p>	
<p>Description: 650MM HYDRO Customer Approval Drawing</p> <p>Drawn By: G GIBBONS</p> <p>Drawn Date: 5/13/2007</p> <p>Scale: 1:2</p> <p>Last saved by: gibbons Last saved on: Tuesday, June 17, 2008 8:12:55 AM</p>		<p>SEE INDIVIDUAL PART PRINTS</p> <p>Used on: 650 MM HYDRO</p> <p>Sheet 1 of 1</p>	