


NOTE:
STANDARD MOUNTING POSITION FOR ALL UMS TURNABLE MODELS IS WITH HYDRAULIC DRIVE LOCATED IN THE 6:00 O'CLOCK POSITION. HYDRAULIC MOTOR CAN BE MOUNTED ON EITHER FRONT OR BACK OF TURNTABLE AND IS EASILY CHANGED.

OPTIONAL TURNTABLE MOUNTING POSITIONS ARE POSSIBLE BUT MAY REQUIRE LONGER HYDRAULIC HOSES AND SENSOR CONNECTIONS AND MAY ALSO REQUIRE MODIFICATION OF EXISTING MACHINE GUARDS, COVERS AND SAFETY INTERLOCK SYSTEMS.

APPROVAL PRINT REFERENCES ARE TO
MODEL # _____
SERIAL # _____

PLEASE CHECK PRINT DIMENSIONS CAREFULLY. NOTE AND INITIAL ANY CHANGES OR CORRECTIONS PROMPT RETURN EXPEDITES DELIVERY OF YOUR ORDER.

APPD. BY _____ DATE _____

 MGS MFG. GROUP ENGINEERING FOR OPTIMUM PERFORMANCE <small>W180 N11701 Maple Rd. Germantown, WI 53022 Phone: (262) 255-8790</small>	
<small>PROPRIETARY & CONFIDENTIAL</small> This is proprietary and confidential material which is the sole property of MGS Mfg. Co. 2002 and may not, under any circumstance, be reproduced or converted for any other use without the express written approval of MGS Mfg. Co. <small>TOLERANCES UNLESS OTHERWISE SPECIFIED</small> 1 Pk. Deciml ± .1 2 Pk. Deciml ± .01 3 Pk. Deciml ± .005 4 Pk. Deciml ± .0005 Anglkw: ± 1°	Description: 750 MM Hydro Customer Approval Drawing Mgt1: SEE INDIVIDUAL PART DRAWINGS Drawn By: G GIBBONS Date: 9/5/2006 Scale: 1:4 Last saved by: gibbonsg Last saved on: Friday, June 20, 2008 1:30:04 PM
Sheet 1 of 1	